

# AR4260

## Bullet Camera


Newly developed premium 2 megapixel bullet camera, advanced light metering and professional video image quality.

Small factor bullet camera in 1920x1080 resolution fully featured including IP67 metal housing with cable managed bracket and advanced IR light.

Triple stream in HDTV/1080p. with best color image and balance.



- 1/2,5" Bigger size Aptina sensor
- 1920x1080 at 30fps.
- Advanced T.I. DSP processor
- Triple stream H.264/MJPEG/MPEG4
- Real time video (HDTV) 1080p.
- IP67 Heavy duty professional housing
- DigitalWDR
- Cable managed bracket
- 3rd. Gen. infrared light, 35m.
- Micro SD/SDHC/SDXC local storage
- POE/DC power supply
- Varifocal, high resolution, autoiris lens
- Analogue output for easy installation
- Alarm I/O



### Camera

Type	Bullet camera, metal casting body, IP67 weather proof, IR light 35m.	
Image Sensor	1/2,5" progressive CMOS	
Picture Elements	1920(H) x 1200(V)	
Minimum Illumination	Color	0.4 LUX @ F1.2
	B/W	0.2 LUX @ F1.2
	IR ON	0 Lux
Shutter Speed	Automatic, Manual 1/7,5 ~ 1/100,000 seg.	
White Balance	Automatic, settings	
Gain Control	Automatic	

Lens		
Megapixel		Yes
Day/Night		Yes
Lens Type		Varifocal
Focal Length		3-10,5mm.
Maximum Aperture		F1,4
Mount		Φ14 Mount
Image Format		1/2,7"
Operation	Focus	Manual
	Zoom	Manual
	Iris	DC iris
Operation		
Video Compression		H.264, MJPEG, MPEG4
Video Stream		Triple stream
Frame Rate		30 fps.
Image Setting		Brightness, Contrast, Sharpness, White balance, Flicker, Image flip, Shutter speed, Back light compensation, Software WDR
Audio Compression		G.711, AAC-LC
Two-way Audio		Yes
Alarm Input		1 input
Alarm Output		1 digital output
Bit rate		64-7000Kb.
Video Resolution		
Main Stream		1920x1080
Sub Stream		1600x1200, 1280x1024, 1280x720, 720x480, 640x480, 320x192
Network		
Interface		10/100 Ethernet
Protocol		TCP/IP, SMTP, FTP, HTTP, RTP/RTSP, RTCP, IPv4, UPnP, NTP, ICMP, DHCP
Mechanical		
Connectors	Power	DC Power Jack, PoE
	Ethernet	RJ-45
	Audio	By adding external Audio In and Audio Out cable
	Digital I/O / RS485	6 pin terminal block
	Auto Iris	Yes
	Local Storage	Micro SD/SDHC/SDXC class 4 or above
LED Indicator	TV -Out	BNC, resolution 640x480
		2 LED, power/status
General		
Environment Temperature		-10~50°C.
Humidity		10-90% Not condensing
Power Source		12V DC / PoE
Max. Power Consumption		5,5-9,2W. DC / 6,1-10,1W. PoE
Dimensions (L X W X H)		195.7 X 74.6 X 169.9
Weight		830g.
Regulatory		CE, FCC, RoHS compliant
Power over Ethernet		
PoE Standard		IEEE 802.3af
PoE Power Supply Type		End-span / Mid-span
Web Interface		
Installation Management		Web based configuration
Maintenance		Upgrade through web browser
Access from Web Browser		Camera live view, video recording, video settings, bandwidth control, image snapshot, audio, video/image schedule recording, alarms, tect overlay, network settings
Language		English, Spanish, Arabic, Traditional Chinese, Turkish, Hebrew, French, Russian, Vietnamese
Applications		
Network Storage		Arlotto NVR devices
Live Viewing		IE
CMS Server support		Qgard and Arlotto CMS
Platform		
Standard		Onvif 2.4, PSIA, Profile S
SDK		Available



### Arlotto Comnet Inc.

No. 54 Park Avenue 2. Hsinchu Science Park  
 30075 Hsinchu, Taiwan  
 Tel:+886-3-5678020 | Fax:+886-3-5678019  
 email: sales@arlotto.com.tw